

MADO 240 LED DOWNLIGHT

KEY FEATURES

- Professional LED downlight
- UGR <19 in accordance with EN-12464: 1 (workplace lighting requirements)
- External LED driver
- 5 year Pragmalux Warranty



DETAILS



Reflector



Installation detail

IP20 IP44 IK02      CRI ≥80

5 PRAGMALUX
YEAR
WARRANTY

OPTIONS



COLORS



2700K 3000K 5000K CRI>90

IP65

SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	LIFETIME L80B10	BEAM ANGLE	IP
3501575	LED Downlight MADO 240 12W 3000K 1777lm Ø240 Z:200 †100 Darklight	12	1777	148	3000	100000	79°	20
3501581	LED Downlight MADO 240 12W 4000K 1869lm Ø240 Z:200 †100 Darklight	12	1869	156	4000	100000	79°	20
3501576	LED Downlight MADO 240 18W 3000K 2486lm Ø240 Z:200 †100 Darklight	18	2486	138	3000	100000	79°	20
3501582	LED Downlight MADO 240 18W 4000K 2612lm Ø240 Z:200 †100 Darklight	18	2612	145	4000	100000	79°	20
3501577	LED Downlight MADO 240 25W 3000K 3395lm Ø240 Z:200 †100 Darklight	25	3395	136	3000	100000	79°	20
3501583	LED Downlight MADO 240 25W 4000K 3566lm Ø240 Z:200 †100 Darklight	25	3566	143	4000	100000	79°	20
3501578	LED Downlight MADO 240 33W 3000K 4248lm Ø240 Z:200 †100 Darklight	33	4248	129	3000	100000	79°	20
3501584	LED Downlight MADO 240 33W 4000K 4460lm Ø240 Z:200 †100 Darklight	33	4460	135	4000	100000	79°	20
3501579	LED Downlight MADO 240 39W 3000K 4890lm Ø240 Z:200 †100 Darklight	39	4890	125	3000	100000	79°	20
3501585	LED Downlight MADO 240 39W 4000K 5048lm Ø240 Z:200 †100 Darklight	39	5048	129	4000	100000	79°	20
3501563	LED Downlight MADO 240 12W 3000K 1545lm Ø240 Z:200 †100 Matt	12	1454	121	3000	100000	74°	44
3501569	LED Downlight MADO 240 12W 4000K 1625lm Ø240 Z:200 †100 Matt	12	1625	135	4000	100000	74°	44
3501564	LED Downlight MADO 240 18W 3000K 2160lm Ø240 Z:200 †100 Matt	18	2160	120	3000	100000	74°	44
3501570	LED Downlight MADO 240 18W 4000K 2270lm Ø240 Z:200 †100 Matt	18	2270	126	4000	100000	74°	44
3501565	LED Downlight MADO 240 25W 3000K 2950lm Ø240 Z:200 †100 Matt	25	2950	118	3000	100000	74°	44
3501571	LED Downlight MADO 240 25W 4000K 3100lm Ø240 Z:200 †100 Matt	25	3100	124	4000	100000	74°	44
3501566	LED Downlight MADO 240 33W 3000K 3960lm Ø240 Z:200 †100 Mat	33	3960	120	3000	100000	74°	44
3501572	LED Downlight MADO 240 33W 4000K 3875lm Ø240 Z:200 †100 Matt	33	3875	117	4000	100000	74°	44
3501567	LED Downlight MADO 240 39W 3000K 4250lm Ø240 Z:200 †100 Matt	39	4250	109	3000	100000	74°	44
3501573	LED Downlight MADO 240 39W 4000K 4385lm Ø240 Z:200 †100 Matt	39	4385	112	4000	100000	74°	44
3501551	LED Downlight MADO 240 12W 3000K 1695lm Ø240 Z:200 †100 Gloss	12	1454	121	3000	100000	83°	44
3501557	LED Downlight MADO 240 12W 4000K 1780lm Ø240 Z:200 †100 Gloss	12	1625	135	4000	100000	83°	44
3501552	LED Downlight MADO 240 18W 3000K 2370lm Ø240 Z:200 †100 Gloss	18	2160	120	3000	100000	83°	44
3501558	LED Downlight MADO 240 18W 4000K 2490lm Ø240 Z:200 †100 Gloss	18	2270	126	4000	100000	83°	44
3501553	LED Downlight MADO 240 25W 3000K 3235lm Ø240 Z:200 †100 Gloss	25	2950	118	3000	100000	83°	44
3501559	LED Downlight MADO 240 25W 4000K 3395lm Ø240 Z:200 †100 Gloss	25	3100	124	4000	100000	83°	44
3501554	LED Downlight MADO 240 33W 3000K 4045lm Ø240 Z:200 †100 Gloss	33	3960	120	3000	100000	83°	44
3501560	LED Downlight MADO 240 33W 4000K 4250lm Ø240 Z:200 †100 Gloss	33	3875	117	4000	100000	83°	44

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: February 2021

MADO 240 LED DOWNLIGHT

PRAGMALUX
PROFESSIONAL LIGHTING

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	LIFETIME L80B10	BEAM ANGLE	IP
3501555	LED Downlight MAD0 240 39W 3000K 4655lm Ø240 Z:200 †100 Gloss	39	4250	109	3000	100000	83°	44
3501561	LED Downlight MAD0 240 39W 4000K 4810lm Ø240 Z:200 †100 Gloss	39	4385	112	4000	100000	83°	44

TECHNICAL DATA

ELECTRICAL DATA

Voltage (V)	220-240
Frequency (Hz)	50/60
Power factor (λ)	≥0.95
Operating mode	External LED Driver


TEMPERATURES & OPERATING CONDITIONS

Ambient temperature	25°C
---------------------	------

COLORS & MATERIALS

Color (Housing)	White
Material (Housing)	Aluminum
Material (Reflector)	Aluminum

DIMENSIONS



CERTIFICATES & STANDARDS

Driver certificates	CE
Fixture certificates	CE
Ingress protection	IP20 / IP44
Protection class	II
Protection class IK	02
IEC	EN IEC 62722-2-1
LM80 (TM21) L90B50 (hours)	>50,000

CAPABILITIES

Dimmable	No / Yes
LED Module replacable	No

EXTRA INFORMATION



Darklight version





Darklight reflector version



Gloss version

PHOTOMETRIC SPECIFICATIONS

LED DOWNLIGHT MAD0 240 25W 3000K MATT



874/2012

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: February 2021

Page 2/2