



### KEY FEATURES

- Special 90° spiral lens optic for homogeneous light distribution
- IP65 waterproof, suitable for dusty and humid environments
- Long life of 76,000 hours
- Plug & Play installation 3-pole IP68 screwless connector
- Integrated premium LED Driver Philips Xitanium + Philips Lumileds chips
- Standard 1-10V Dimmable
- Up to 140 lumens per watt
- 5 years Pragmalux warranty

IP65 IK08 650° GWT 140LM/W 1-10V 90°

**5** PRAGMALUX  
YEAR  
WARRANTY

### DETAILS



Back



Spiral lens

### OPTIONS



3000K 5000K



### ACCESSORIES



Reflector Alu  
4605111



Prisma reflector  
4607825



Adjustable bracket  
4605623  
4605104



Daylight sensor  
4607092



IP68 connector  
included

### SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	CRI	INPUT CURRENT	LIFETIME L80B10	EQUIVALENT	BEAM ANGLE
4605067	LED Highbay Storm 100W 4000K 90° 1-10V Dim Black	100	14000	140	4000	≥80	0.46	76000	200W	90°
4605074	LED Highbay Storm 120W 4000K 90° 1-10V Dim Black	120	16800	140	4000	≥80	0.55	76000	250W	90°
4605081	LED Highbay Storm 150W 4000K 90° 1-10V Dim Black	150	21000	140	4000	≥80	0.69	76000	250W	90°
4605098	LED Highbay Storm 200W 4000K 90° 1-10V Dim Black	200	28000	140	4000	≥80	0.91	76000	400W	90°

### TECHNICAL DATA

ELECTRICAL DATA	
Voltage (V)	220-240
Frequency (Hz)	50/60
Power factor (λ)	≥0.90
Operating mode	Integrated LED Driver
Electrical connection	Max 3x1,0 mm <sup>2</sup> wire
Total harmonic distortion	≤ 15 %

### TEMPERATURES & OPERATING CONDITIONS

Ambient temperature	25°C
Operating temperature	-30 ~ +45°C
Storage temperature	-30 ~ +80°C

### COLORS & MATERIALS

Color ( Housing)	Black RAL9017
Material ( Housing)	Aluminum
Material ( Reflector)	PC

ITEM CODE	DESCRIPTION	DRIVER FAILURE RATE AT 5,000H	INRUSH CURRENT IPEAK (A)	INRUSH CURRENT TWIDTH (μs)	MAX. NO. OF DRIVERS ON MCB TYPE B 10A	MAX. NO. OF DRIVERS ON MCB TYPE B 16A	MAX. NO. OF DRIVERS ON MCB TYPE C 10A	MAX. NO. OF DRIVERS ON MCB TYPE C 16A
4605067	LED Highbay Storm 100W 4000K 90° 1-10V Dim Black	≤1%	53	180	9	15	15	25
4605074	LED Highbay Storm 120W 4000K 90° 1-10V Dim Black	≤1%	55	214	5	9	9	15
4605081	LED Highbay Storm 150W 4000K 90° 1-10V Dim Black	≤1%	55	214	5	9	9	15
4605098	LED Highbay Storm 200W 4000K 90° 1-10V Dim Black	≤1%	56	326	3	5	5	8

### PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020


### CERTIFICATES & STANDARDS

Driver certificates	CE
Fixture certificates	CE
Ingress protection	IP65
Protection class	I
Protection class IK	08
Glow Wire Test ( IEC 695-2-1)	650°C
Photobiological safety group EN62778	RG1

### CAPABILITIES


UGR	≤25-30
Dimmable	1-10V
Type of connection	Push Terminal, 3-pole
LED Module replacable	No
Installation	Hook / Ceiling Mounting (±45°C/±90°C) / Wall Mounting

## DIMENSIONS




## PHOTOMETRIC SPECIFICATIONS


### LED HIGHBAY STORM 100W 4000K 90° 1-10V DIM BLACK



### LED HIGHBAY STORM 120W 4000K 90° 1-10V DIM BLACK



### LED HIGHBAY STORM 150W 4000K 90° 1-10V DIM BLACK



### LED HIGHBAY STORM 200W 4000K 90° 1-10V DIM BLACK

