



## KEY FEATURES

- Equipped with a total Philips system: Xitanium LED Drivers, Fortimo PCB and LED chips
- Suitable for suspended ceilings with visible profiles
- Shielding made of high-quality PMMA material
- Very high lumen / watt ratio, or efficacy > 125 lm / w
- Very low glare UGR <16 in accordance with EN-12464-1 (workplace lighting requirements)
- Very high color consistency / binning / SDCM <3
- Plug & play connection via Wieland GST18i3 or GST18i5
- 5 year Pragmalux Warranty

IP20 IK02  $\triangle$  UGR<19  
80°

**5** PRAGMALUX  
YEAR  
WARRANTY

## OPTIONS



## SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	CRI	LIFETIME L80B10	BEAM ANGLE
74310301	LED Panel Lino 60x60 13-34W 1600-4250lm 830	13-34	1600-4250	125	3000	≥80	100000	80°
74410301	LED Panel Lino60x60 13-34W 1600-4250lm 840	13-34	1600-4250	125	4000	≥80	100000	80°
74610301	LED Panel Lino60x60 13-34W 1600-4250lm 865	13-34	1600-4250	125	3000	≥80	100000	80°
84310301	LED Panel Lino60x60 13-34W 1600-4250lm 830 DALI	13-34	1600-4250	125	4000	≥80	100000	80°
84410301	LED Panel Lino60x60 13-34W 1600-4250lm 840 DALI	13-34	1600-4250	125	3000	≥80	100000	80°
84610301	LED Panel Lino60x60 13-34W 1600-4250lm 865 DALI	13-34	1600-4250	125	4000	≥80	100000	80°

## DIMENSIONS

