



KEY FEATURES

- Equipped with a total Tridonic system: High end Tridonic LED Drivers, PCB and LED chips
- Suitable for suspended ceilings with visible profiles
- Very unique design which mimics the idea of a skylight
- Very high lumen / watt ratio, or efficacy > 125 lm / w
- Very low glare UGR <19 in accordance with EN-12464-1 (workplace lighting requirements)
- Very high color consistency / binning / SDCM <3
- Plug & play connection via Wieland GST18i3 or GST18i5
- 5 year Pragmalux Warranty

IP20 IK02 \triangle UGR<19

5 PRAGMALUX
YEAR
WARRANTY

OPTIONS



SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	CRI	LIFETIME L80B10	BEAM ANGLE
74330301	LED Panel Sky 60x60 35W 1600-4250lm 830	13-34	1600-4250	125	3000	≥80	100000	80°
74340301	LED Panel Sky 60x60 35W 1600-4250lm 840	13-34	1600-4250	125	4000	≥80	100000	80°
74360301	LED Panel Sky 60x60 35W 1600-4250lm 865	13-34	1600-4250	125	6500	≥80	100000	80°
84330301	LED Panel Sky 60x60 35W 1600-4250lm 830 DALI	13-34	1600-4250	125	3000	≥80	100000	80°
84330301	LED Panel Sky 60x60 35W 1600-4250lm 840 DALI	13-34	1600-4250	125	4000	≥80	100000	80°
84330301	LED Panel Sky 60x60 35W 1600-4250lm 865 DALI	13-34	1600-4250	125	6500	≥80	100000	80°

ELECTRICAL DATA

Voltage (V)	220-240
Frequency (Hz)	50/60
Power factor (λ)	≥0.90
Operating mode	External LED Driver
Total harmonic distortion	≤ 20 %

CERTIFICATES & STANDARDS

Driver certificates	CE
Fixture certificates	CE
Ingress protection	IP20
Protection class	II
Protection class IK	02
Photobiological safety group EN62778	RG0
IEC	EN IEC 62722-2-1
LM80 (TM21) / L90B50 (hours)	>50,000

TEMPERATURES & OPERATING CONDITIONS

Ambient temperature	25°C
Operating temperature	-10 ~ +40°C



CAPABILITIES

UGR	≤19
Dimmable	No / DALI
LED Module replacable	No

COLORS & MATERIALS

Color (Housing)	White
Material (Housing)	Steel
Material (Reflector)	PC

DIMENSIONS



PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: February 2021

Page 1/1