

LONO 260 LED DOWNLIGHT

PRAGMALUX
PROFESSIONAL LIGHTING



KEY FEATURES

- Professional LED downlight
- External LED driver
- 5 year Pragmalux Warranty

DETAILS



Reflector



Reflector

IP40 IK02    CRI ≥80

5 PRAGMALUX
YEAR
WARRANTY

OPTIONS



2700K 3000K 5000K CRI>90

IP54

COLORS



SPECIFICATIONS (ACCORDING TO EN IEC 62722-2-1)

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	LIFETIME L80	BEAM ANGLE
3501465	LED Downlight LONO 260 9W 3000K 1260lm Ø260 Z:237 ↑180	9	1260	140	3000	76000	72°
3501466	LED Downlight LONO 260 9W 4000K 1330lm Ø260 Z:237 ↑180	9	1330	148	4000	76000	72°
3501467	LED Downlight LONO 260 12W 3000K 1755lm Ø260 Z:237 ↑180	12	1755	146	3000	76000	72°
3501468	LED Downlight LONO 260 12W 4000K 1850lm Ø260 Z:237 ↑180	12	1850	154	4000	76000	72°
3501469	LED Downlight LONO 260 18W 3000K 2460lm Ø260 Z:237 ↑180	18	2460	137	3000	76000	72°
3501470	LED Downlight LONO 260 18W 4000K 2580lm Ø260 Z:237 ↑180	18	2580	143	4000	76000	72°
3501471	LED Downlight LONO 260 25W 3000K 3355lm Ø260 Z:237 ↑180	25	3355	134	3000	76000	72°
3501472	LED Downlight LONO 260 25W 4000K 3525lm Ø260 Z:237 ↑180	25	3525	141	4000	76000	72°
3501473	LED Downlight LONO 260 33W 3000K 4200lm Ø260 Z:237 ↑180	33	4200	127	3000	76000	72°
3501474	LED Downlight LONO 260 33W 4000K 4410lm Ø260 Z:237 ↑180	33	4410	134	4000	76000	72°
3501475	LED Downlight LONO 260 39W 3000K 4830lm Ø260 Z:237 ↑180	39	4830	124	3000	76000	72°
3501476	LED Downlight LONO 260 39W 4000K 4990lm Ø260 Z:237 ↑180	39	4990	128	4000	76000	72°

TECHNICAL DATA

ELECTRICAL DATA

Voltage (V)	220-240
Frequency (Hz)	50/60
Power factor (λ)	≥0.95
Operating mode	External LED Driver

TEMPERATURES & OPERATING CONDITIONS

Ambient temperature	25°C
---------------------	------

COLORS & MATERIALS

Color (Housing)	White
Material (Housing)	Metal
Material (Reflector)	Aluminum

CERTIFICATES & STANDARDS

Driver certificates	CE
Fixture certificates	CE
Ingress protection	IP40-44
Protection class	II
IEC	EN IEC 62722-2-1
LM80 (TM21) L90B50 (hours)	>50,000

CAPABILITIES


Dimmable	No / Yes
LED Module replacable	No

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: February 2021

DIMENSIONS



PHOTOMETRIC SPECIFICATIONS

LED DOWNLIGHT LONO 260 25W 3000K

