



## KEY FEATURES

- High quality LED ceiling and wall fixture
- Lifetime 50,000 hours
- Integrated LED driver
- Uniform light distribution
- PMMA diffuser
- Possible through-wiring
- Loop in Loop out
- Installation on wall and/or ceiling
- 5 year Pragmalux Warranty


IP44 IK03  650° GWT 94LM/W  120°

**5** PRAGMALUX  
YEAR  
WARRANTY

## DETAILS



Connector



Emergency

## OPTIONS



## ACCESSORIES



PMMA Cover

## SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	CRI	INPUT CURRENT	LIFETIME L80B10	BEAM ANGLE
4605654	LED Bulkhead Polo IP44 8W 3000K Ø180mm	8	650	81	3000	≥80	0.08	50000	120°
4605661	LED Bulkhead Polo IP44 8W 4000K Ø180mm	8	700	88	4000	≥80	0.08	50000	120°
4608334	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm	12	1000-1100	83-92	3000/4000/6000	≥80	0.06	50000	120°
4608334-S	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm Sensor	12	1000-1100	83-92	3000/4000/6000	≥80	0.06	50000	120°
4608334-N	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm Emergency	12	1000-1100	83-92	3000/4000/6000	≥80	0.06	50000	120°
4608334-SN	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm Sensor+Emergency	12	1000-1100	83-92	3000/4000/6000	≥80	0.06	50000	120°
4608341	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm	18	1550-1700	86-94	3000/4000/6000	≥80	0.09	50000	120°
4608341-S	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm Sensor	18	1550-1700	86-94	3000/4000/6000	≥80	0.09	50000	120°
4608341-N	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm Emergency	18	1550-1700	86-94	3000/4000/6000	≥80	0.09	50000	120°
4608341-SN	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm Sensor+Emergency	18	1550-1700	86-94	3000/4000/6000	≥80	0.09	50000	120°
4608358	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm	22	1950-2150	89-98	3000/4000/6000	≥80	0.11	50000	120°
4608358-S	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm Sensor	22	1950-2150	89-98	3000/4000/6000	≥80	0.11	50000	120°
4608358-N	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm Emergency	22	1950-2150	89-98	3000/4000/6000	≥80	0.11	50000	120°
4608358-SN	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm Sensor+Emergency	22	1950-2150	89-98	3000/4000/6000	≥80	0.11	50000	120°

## PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: March 2021

## TECHNICAL DATA

### ELECTRICAL DATA

Voltage (V)	220-240
Frequency (Hz)	50/60
Power factor (λ)	≥0.9 / ≥0.8 with sensor
Operating mode	Integrated LED Driver
Electrical connection	Max 3x2,5 mm² wire
Total harmonic distortion	≤ 20 %

### TEMPERATURES & OPERATING CONDITIONS

Ambient temperature	25°C
Operating temperature	-20 ~ +40°C
Storage temperature	-20 ~ +60°C

### COLORS & MATERIALS

Color ( Housing)	White RAL9016
Material ( Housing)	Steel
Material ( Reflector)	PMMA

### CERTIFICATES & STANDARDS

Driver certificates	CE
Fixture certificates	CE
Ingress protection	IP44
Protection class	II
Protection class IK	03
Glow Wire Test ( IEC 695-2-1)	650°C
Photobiological safety group EN62778	RG0

### CAPABILITIES

UGR	≤25
Dimmable	No
Type of connection	Push Terminal, 2-pole
LED Module replaceable	No
Installation	Through-wiring Possible


ITEM CODE	DESCRIPTION	DRIVER FAILURE RATE AT 5,000H	INRUSH CURRENT IPEAK (A)	INRUSH CURRENT TWIDTH (µs)	MAX. NO. OF DRIVERS ON MCB TYPE B 10A	MAX. NO. OF DRIVERS ON MCB TYPE B 16A	MAX NO.OF DRIVERS ON MCB TYPE C 10A	MAX. NO. OF DRIVERS ON MCB TYPE C 16A
4605654	LED Bulkhead Polo IP44 8W 3000K Ø180mm	≤1%	9.68	194	100	160	100	160
4605661	LED Bulkhead Polo IP44 8W 4000K Ø180mm	≤1%	9.68	194	100	160	100	160
4608334	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm	≤1%	3.32	72	106	170	106	170
4608334-S	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm Sensor	≤1%	3.32	72	106	170	106	170
4608334-N	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm Emergency	≤1%	3.32	72	106	170	106	170
4608334-SN	LED Bulkhead Polo G2 IP44 12W 3000K-6000K 3-CCT Ø280mm Sensor+Emergency	≤1%	3.32	72	106	170	106	170
4608341	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm	≤1%	6.24	72	66	106	66	106
4608341-S	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm Sensor	≤1%	6.24	72	66	106	66	106
4608341-N	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm Emergency	≤1%	6.24	72	66	106	66	106
4608341-SN	LED Bulkhead Polo G2 IP44 18W 3000K-6000K 3-CCT Ø360mm Sensor+Emergency	≤1%	6.24	72	66	106	66	106
4608358	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm	≤1%	7.69	72	53	85	53	85
4608358-S	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm Sensor	≤1%	7.69	72	53	85	53	85
4608358-N	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm Emergency	≤1%	7.69	72	53	85	53	85
4608358-SN	LED Bulkhead Polo G2 IP44 22W 3000K-6000K 3-CCT Ø410mm Sensor+Emergency	≤1%	7.69	72	53	85	53	85

## PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.


Version: March 2021

## DIMENSIONS




## PHOTOMETRIC SPECIFICATIONS

### LED BULKHEAD POLO 12W 4000K



### LED BULKHEAD POLO 18W 4000K



### LED BULKHEAD POLO 22W 4000K

