

MADO SURFACE LED DOWNLIGHT

PRAGMALUX
PROFESSIONAL LIGHTING



KEY FEATURES

- Professional LED SURFACE downlight
- External LED driver
- 5 year Pragmalux Warranty

DETAILS



Reflector

IP40 IK02    CRI ≥ 80

5 PRAGMALUX
YEAR
WARRANTY

OPTIONS



COLORS



2700K 3000K 5000K CRI > 90

SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	LIFETIME L80B10	BEAM ANGLE
3501451	LED Downlight MADO Surface 5W 3000K 635lm Ø130 ↓140 Matt	5	635	127	3000	50000	73°
3501452	LED Downlight MADO Surface 5W 4000K 665lm Ø130 ↓140 Matt	5	665	133	4000	50000	73°
3501238	LED Downlight MADO Surface 9W 3000K 1025lm Ø130 ↓140 Matt	9	1025	114	3000	50000	73°
3501252	LED Downlight MADO Surface 9W 4000K 1075lm Ø130 ↓140 Matt	9	1075	119	4000	50000	73°
3501253	LED Downlight MADO Surface 13W 3000K 1390lm Ø130 ↓140 Matt	13	1390	107	3000	50000	73°
3501239	LED Downlight MADO Surface 13W 4000K 1460lm Ø130 ↓140 Matt	13	1460	112	4000	50000	73°
3501453	LED Downlight MADO Surface 19W 3000K 1900lm Ø130 ↓140 Matt	19	1900	100	3000	50000	73°
3501454	LED Downlight MADO Surface 19W 4000K 1985lm Ø130 ↓140 Matt	19	1985	104	4000	50000	73°
3501455	LED Downlight MADO Surface 9W 3000K 1125lm Ø160 ↓150 Matt	9	1125	125	3000	50000	77°
3501456	LED Downlight MADO Surface 9W 4000K 1185lm Ø160 ↓150 Matt	9	1185	132	4000	50000	77°
3501246	LED Downlight MADO Surface 12W 3000K 1565lm Ø160 ↓150 Matt	12	1565	130	3000	50000	77°
3501247	LED Downlight MADO Surface 12W 4000K 1645lm Ø160 ↓150 Matt	12	1645	137	4000	50000	77°
3501248	LED Downlight MADO Surface 18W 3000K 2190lm Ø160 ↓150 Matt	18	2190	122	3000	50000	77°
3501249	LED Downlight MADO Surface 18W 4000K 2300lm Ø160 ↓150 Matt	18	2300	128	4000	50000	77°
3501457	LED Downlight MADO Surface 25W 3000K 2990lm Ø160 ↓150 Matt	25	2990	120	3000	50000	77°
3501458	LED Downlight MADO Surface 25W 4000K 3140lm Ø160 ↓150 Matt	25	3140	126	4000	50000	77°
3501459	LED Downlight MADO Surface 9W 3000K 1110lm Ø205 ↓190 Matt	9	1110	123	3000	50000	74°
3501460	LED Downlight MADO Surface 9W 4000K 1170lm Ø205 ↓190 Matt	9	1170	130	4000	50000	74°
3501330	LED Downlight MADO Surface 12W 3000K 1545lm Ø205 ↓190 Matt	12	1545	129	3000	50000	74°
3501337	LED Downlight MADO Surface 12W 4000K 1625lm Ø205 ↓190 Matt	12	1625	135	4000	50000	74°
3501461	LED Downlight MADO Surface 18W 3000K 2160lm Ø205 ↓190 Matt	18	2160	120	3000	50000	74°
3501462	LED Downlight MADO Surface 18W 4000K 2270lm Ø205 ↓190 Matt	18	2270	126	4000	50000	74°
3501348	LED Downlight MADO Surface 25W 3000K 2950lm Ø205 ↓190 Matt	25	2950	118	3000	50000	74°
3501360	LED Downlight MADO Surface 25W 4000K 3100lm Ø205 ↓190 Matt	25	3100	124	4000	50000	74°
3501463	LED Downlight MADO Surface 33W 3000K 3690lm Ø205 ↓190 Matt	33	3690	112	3000	50000	74°
3501464	LED Downlight MADO Surface 33W 4000K 3875lm Ø205 ↓190 Matt	33	3875	117	4000	50000	74°
3501335	LED Downlight MADO Surface 12W 4000K 1625lm Ø205 ↓190 Cross	39	4385	112	4000	50000	93°
3501374	LED Downlight MADO Surface 18W 3000K 2160lm Ø205 ↓190 Cross	12	1545	129	3000	50000	93°

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020


Page 1/2

MADO SURFACE LED DOWNLIGHT

PRAGMALUX
PROFESSIONAL LIGHTING

ITEM CODE	DESCRIPTION	W	LM	LM/W	KELVIN	LIFETIME L80B10	BEAM ANGLE
3501346	LED Downlight MADO Surface 25W 3000K 2950lm Ø205 ↓190 Cross	18	2160	120	3000	50000	93°
3501358	LED Downlight MADO Surface 25W 4000K 3100lm Ø205 ↓190 Cross	18	2270	126	4000	50000	93°

DIMENSIONS




EXTRA INFORMATION



PHOTOMETRIC SPECIFICATIONS

LED DOWNLIGHT MADO SURFACE 25W 3000K MATT



PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020

