



## KEY FEATURES

- Equipped with a total Philips system: Xitanium LED Drivers, Fortimo PCB and LED chips
- Suitable for suspended ceilings with visible profiles
- The highest quality aluminum reflector MIRO-Silver® for 98% reflection
- Shielding made of high-quality PMMA material
- Very high lumen / watt ratio, or efficacy > 125 lm / w
- Very low glare UGR < 16 in accordance with EN-12464-1 (workplace lighting requirements)
- Very high color consistency / binning / SDCM < 3
- Plug & play connection via Wieland GST18i3 or GST18i5
- 5 year Pragmalux Warranty

IP20 IK02  UGR<19

**5** PRAGMALUX  
YEAR  
WARRANTY

## OPTIONS



## SPECIFICATIONS

| ITEM CODE | DESCRIPTION                                        | W     | LM        | LM/W | KELVIN | CRI | LIFETIME<br>L80B10 | BEAM<br>ANGLE |
|-----------|----------------------------------------------------|-------|-----------|------|--------|-----|--------------------|---------------|
| 71310301  | LED Panel Unico 60x60 13-34W 1600-4250lm 830       | 13-34 | 1600-4250 | 125  | 3000   | ≥80 | 100000             | 80°           |
| 71410301  | LED Panel Unico 60x60 13-34W 1600-4250lm 840       | 13-34 | 1600-4250 | 125  | 4000   | ≥80 | 100000             | 80°           |
| 71610301  | LED Panel Unico 60x60 13-34W 1600-4250lm 865       | 13-34 | 1600-4250 | 125  | 6500   | ≥80 | 100000             | 80°           |
| 81310301  | LED Panel Unico 60x60 13-34W 1600-4250lm 830 DALI  | 13-34 | 1600-4250 | 125  | 3000   | ≥80 | 100000             | 80°           |
| 81410301  | LED Panel Unico 60x60 13-34W 1600-4250lm 840 DALI  | 13-34 | 1600-4250 | 125  | 4000   | ≥80 | 100000             | 80°           |
| 81610301  | LED Panel Unico 60x60 13-34W 1600-4250lm 865 DALI  | 13-34 | 1600-4250 | 125  | 6500   | ≥80 | 100000             | 80°           |
| 71310302  | LED Panel Unico 30x120 13-34W 1600-4250lm 830      | 13-34 | 1600-4250 | 125  | 3000   | ≥80 | 100000             | 80°           |
| 71410302  | LED Panel Unico 30x120 13-34W 1600-4250lm 840      | 13-34 | 1600-4250 | 125  | 4000   | ≥80 | 100000             | 80°           |
| 71610302  | LED Panel Unico 30x120 13-34W 1600-4250lm 865      | 13-34 | 1600-4250 | 125  | 6500   | ≥80 | 100000             | 80°           |
| 81310302  | LED Panel Unico 30x120 13-34W 1600-4250lm 830 DALI | 13-34 | 1600-4250 | 125  | 3000   | ≥80 | 100000             | 80°           |
| 81410302  | LED Panel Unico 30x120 13-34W 1600-4250lm 840 DALI | 13-34 | 1600-4250 | 125  | 4000   | ≥80 | 100000             | 80°           |
| 81610302  | LED Panel Unico 30x120 13-34W 1600-4250lm 865 DALI | 13-34 | 1600-4250 | 125  | 6500   | ≥80 | 100000             | 80°           |

## DIMENSIONS

