

PICO ADJUST LED SPOT

PRAGMALUX
PROFESSIONAL LIGHTING



DETAILS



Black version

KEY FEATURES

Pragmalux LED Recessed spotlight Pico is an elegant dimmable recessed spot, where the light source is recessed. Luminaire is IP44 classified and can therefore also be used in the awning or bathroom. The recessed spot is available in a fixed or tiltable (30 °) variant in the colors white or black. This product comes with an external premium Tridonic LED driver.

IP44 IK03



38°

CRI ≥ 90



TILTABLE 30°

INSTALLATION 70 mm

DIMENSIONS 82 mm

5 PRAGMALUX
YEAR
WARRANTY

OPTIONS



GST
1813/5

CASAMBI

COLORS




SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM*	LM/W*	KELVIN	LIFETIME L80B10	BEAM ANGLE
9111838	LED Spot Pico IP44 Tilttable 12W 2700K CRI>90 24D 650lm White Ø82 F - G Ø75 - Dimmable	12	650	54	2700	30000	38°
9111844	LED Spot Pico IP44 Tilttable 12W 2700K CRI>90 24D 650lm Black Ø82 F - G Ø75 - Dimmable	12	650	54	2700	30000	38°
9111840	LED Spot Pico IP44 Tilttable 12W 3000K CRI>90 24D 700lm White Ø82 F - G Ø75 - Dimmable	12	700	58	3000	30000	38°
9111846	LED Spot Pico IP44 Tilttable 12W 3000K CRI>90 24D 700lm Black Ø82 F - G Ø75 - Dimmable	12	700	58	3000	30000	38°
9111842	LED Spot Pico IP44 Tilttable 12W 4000K CRI>90 24D 800lm White Ø82 F - G Ø75 - Dimmable	12	800	67	4000	30000	38°
9111848	LED Spot Pico IP44 Tilttable 12W 4000K CRI>90 24D 800lm Black Ø82 F - G Ø75 - Dimmable	12	800	67	4000	30000	38°

* Bruto lumen - LOR up to 81%

DIMENSIONS



Cutout Size
Adjustable
Ø 70mm

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020

