COB LED STRIP

PRAGMALUX PROFESSIONAL LIGHTING

KEY FEATURES

- Professional flexible LED Strips
- 3M Adhesive
- High quality leds
- Uniform light distribution
- Suitable for use with aluminum profiles
- 3 year Pragmalux Warranty

24V IP20 | MAC ADAM 3 STEPS | 120° | CRI>90 | REEL 5M | WIDTH 8MM | LIFETIME 30.000 HOURS | 3 PRAGMALUX YEAR WARRANTY

SPECIFICATIONS

ITEM CODE	DESCRIPTION	W/M	LM/M	LED'S/M	KELVIN	CRI	MAX. LENGTH NO BRIGHTNESS DIFFERENCE	MIN CUTTABLE LENGHT
9211612	Pragmalux LED Strip COB 24V 5m 544 LED's/m 10W/m 948lm/m 2700K CRI>90	10	948	544	2700	≥90	5m	2,94 cm
9211613	Pragmalux LED Strip COB 24V 5m 544 LED's/m 10W/m 974lm/m 3000K CRI>90	10	974	544	3000	≥90	5m	2,94 cm
9211614	Pragmalux LED Strip COB 24V 5m 544 LED's/m 10W/m 1046lm/m 4000K CRI>90	10	1046	544	4000	≥90	5m	2,94 cm

ACCESSORIES

Driver Max.100W 9100222

Driver Max.240W IP65 - 9100296

Driver Max.100W IP67 - 9100305

Driver Max.150W IP67 - 9100505

Driver Max.35W IP67 - 9100284

Driver Max.60W IP67 - 9100304

Driver Max.150W IP67 - 9100304

Driver Max.30W 9100163

Driver Max.60W 9100165

Driver Max.70W 9100206

Driver Max.60W 1-10V - 9100233

RF Controller 4C 9100422

RF Remote 4C 9100423

RF Dimmer Wall 9100425

RF Dimmer Wall 9100427

Profile Alu 8mm 9010609

Profile White 8mm 9011294

Profile Black 8mm 9011295

Profile White 15mm 9011296

Profile Black 15mm 9011297

End Cap 8mm O 9010614

End Cap 8mm O 9011306

End Cap 8mm O 9011307

End Cap 8mm C 9010615

End Cap 8mm C 9011302

End Cap 8mm C 9011303

End Cap 15mm O 9011308

End Cap 15mm O 9011309

End Cap 15mm C 9011304

End Cap 15mm C 9011305

Mounting clip 9010613

PMMA Opal 9010604

PMMA Frosted 9010605

More options available.
Contact our sales department for more information.

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.