

ARIS LED AR111 SPOT

PRAGMALUX
PROFESSIONAL LIGHTING

3 PRAGMALUX
YEAR
WARRANTY



KEY FEATURES

- High quality recessed spot made of aluminum
- 360° rotatable and 40° tiltable
- Removable inner ring for easy installation
- Powder coating finish

IP20 IK02 G53 12V





COLORS



DIMENSIONS

39 mm



COMPATIBLE LAMPS



G53 LED



SPECIFICATIONS

| ITEM CODE | DESCRIPTION | EQUIVALENT | COLOR |
|-----------|--|------------|-------|
| 4604244 | Aris AR111 Spot Round White Ø180mm Cutout Ø150mm 40° Tilttable (Incl. G53 Fitting) | 50W HAL | White |
| 4604251 | Aris AR111 Spot Round Black Ø180mm Cutout Ø150mm 40° Tilttable (Incl. G53 Fitting) | 50W HAL | Black |

TECHNICAL DATA

| ELECTRICAL DATA | |
|-----------------------|-----------------------------|
| Voltage (V) | 12 |
| Frequency (Hz) | 50/60 |
| Max. Power (W) | 50 |
| Operating mode | G53 fitting (included) |
| Electrical connection | 2x 0.75mm ² wire |
| COLORS & MATERIALS | |
| Color (Housing) | White, Black |
| Material (Housing) | Aluminum |

CERTIFICATES & STANDARDS

| | |
|----------------------|------|
| Fixture certificates | CE |
| Ingress protection | IP20 |
| Protection class IK | IK02 |

CAPABILITIES

| | |
|--------------------|---------------------|
| Type of connection | G53 with 25cm cable |
| Installation | 40° Tilttable |

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020

