

# BOXY LED GU10 SPOT

**PRAGMALUX**  
PROFESSIONAL LIGHTING

**3** PRAGMALUX  
YEAR  
WARRANTY



## KEY FEATURES

- High quality recessed spot made of aluminum
- 360° rotatable and 40° tiltable
- Removable inner ring for easy installation
- Powder coating finish

IP20 IK02 GU10 220V  
230V



## COLORS



## ACCESSORIES





Honeycomb  
4608204




Blade clips  
4607849

## DIMENSIONS

25 mm




## COMPATIBLE LAMPS



GU10 LED LED module

## OPTIONS



## SPECIFICATIONS

ITEM CODE	DESCRIPTION	EQUIVALENT	COLOR
4600208	Boxy MR16 Spot White Ø92x92mm Cutout Ø80mm 40° Tilttable (Incl. GU10 Fitting)	50W HAL	White
4600215	Boxy MR16 Spot Black Ø92x92mm Cutout Ø80mm 40° Tilttable (Incl. GU10 Fitting)	50W HAL	Black
4600192	Boxy MR16 Spot Aluminum Ø92x92mm Cutout Ø80mm 40° Tilttable (Incl. GU10 Fitting)	50W HAL	Brushed Alu
4607078	Boxy MR16 Spot Gold Ø92x92mm Cutout Ø80mm 40° Tilttable (Incl. GU10 Fitting)	50W HAL	Gold

## TECHNICAL DATA

ELECTRICAL DATA	
Voltage (V)	220-240
Frequency (Hz)	50/60
Max. Power (W)	50
Operating mode	GU10 fitting (included)
Electrical connection	2x 0.75mm <sup>2</sup> wire

COLORS & MATERIALS	
Color ( Housing)	White, Black, Aluminum, Gold
Material ( Housing)	Aluminum

## CERTIFICATES & STANDARDS

Fixture certificates	CE
Ingress protection	IP20
Protection class IK	IK02

## CAPABILITIES

Type of connection	GU10 with 18cm cable
Installation	40° Tilttable

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020

