

DELTA LED GU10 SPOT

PRAGMALUX
PROFESSIONAL LIGHTING

3 PRAGMALUX
YEAR
WARRANTY



KEY FEATURES


- High quality recessed spot made of aluminum
- 360° rotatable and 40° tiltable
- Removable inner ring for easy installation
- Powder coating finish

IP20 IK02 GU10 220V
230V



DIMENSIONS

46 mm



INSTALLATION
96 mm

DIMENSIONS
106 mm

COLORS



ACCESSORIES




Honeycomb
4608204



Blade clips
4607849

COMPATIBLE LAMPS



GU10 LED LED module

OPTIONS



SPECIFICATIONS

ITEM CODE	DESCRIPTION	EQUIVALENT	COLOR
4604084	Dome Deep MR16 Spot Round White Ø105mm Cutout Ø95mm 40° Tiltable (Incl. GU10 Fitting)	50W HAL	White
4604091	Dome Deep MR16 Spot Round Black Ø105mm Cutout Ø95mm 40° Tiltable (Incl. GU10 Fitting)	50W HAL	Black

TECHNICAL DATA

ELECTRICAL DATA	
Voltage (V)	220-240
Frequency (Hz)	50/60
Max. Power (W)	50
Operating mode	GU10 fitting (included)
Electrical connection	2x 0.75mm ² wire
COLORS & MATERIALS	
Color (Housing)	White, Black
Material (Housing)	Aluminum

CERTIFICATES & STANDARDS

Fixture certificates	CE
Ingress protection	IP20
Protection class IK	IK02


CAPABILITIES

Type of connection	GU10 with 18cm cable
Installation	40° Tilttable

PRAGMALUX

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Power consumption tolerance: +/- 10%.

Version: October 2020



874/2012