# **CINTO ROUND** LED GU10 SURFACE SPOT




## **KEY FEATURES**

COLORS

(W)

B

- High quality surface spot made of aluminum
- Removable reflector and deep design
- · Possible combinations with different color reflectors
- Powder coating finish without visible screws





PRAGMALUX

**B**PRAGMALUX YEAR WARRANTY





#### SPECIFICATIONS

| ITEM CODE | DESCRIPTION                                                            | EQUIVALENT | COLOR |
|-----------|------------------------------------------------------------------------|------------|-------|
| 4606460   | Cinto MR16 Spot Surface Mounted Round Black Ø90mm (Incl. GU10 Fitting) | 50W HAL    | White |
| 4606453   | Cinto MR16 Spot Surface Mounted Round White Ø90mm (Incl. GU10 Fitting) | 50W HAL    | Black |

## TECHNICAL DATA

| ELECTRICAL DATA       |                             |  |  |  |
|-----------------------|-----------------------------|--|--|--|
| Voltage (V)           | 220-240                     |  |  |  |
| Frequency (Hz)        | 50/60                       |  |  |  |
| Max. Power (W)        | 50                          |  |  |  |
| Operating mode        | GU10 fitting (included)     |  |  |  |
| Electrical connection | 2x 0.75mm <sup>2</sup> wire |  |  |  |
|                       |                             |  |  |  |

| COLORS & MATERIALS  |              |  |
|---------------------|--------------|--|
| Color ( Housing)    | White, Black |  |
| Material ( Housing) | Aluminum     |  |

| CERTIFICATES & STANDARDS |      |  |  |  |
|--------------------------|------|--|--|--|
| Fixture certificates     | CE   |  |  |  |
| Ingress protection       | IP20 |  |  |  |
| Protection class IK      | IK02 |  |  |  |

| CAPABILITIES       |                      |  |  |  |
|--------------------|----------------------|--|--|--|
| Type of connection | GU10 with 18cm cable |  |  |  |
| Installation       | Fixed                |  |  |  |



## PRAG<u>MALUX</u>

All rights reserved. Pragmalux - PDL Lighting Group B.V. retains the right to modify product specifications without any prior notice or obligation and does not assume any liability for any consequences of using this document. Subject to errors and printing errors. Luminous flux tolerance: +/- 10%. Version: October 2020